

ST130

LOGISTICS
RETAIL

HEALTH
POSTAL
TEXTILE

Key Features

- Thermal transfer and direct thermal printing technology
- 120mm(4.72inch) paper exit fit for wider print medias
- 300 meters large ribbon capacity
- Auto cutter
- Unique design, rugged and durable printer cation

Specification

PRINT	Print Method	Direct Thermal / Thermal Transfer
	Print Speed	2~6 inch/s (51-152mm/s)
	Interface	USB+Parallel+Serial +Ethernet
	Print Resolution	203 dpi
	Dot Size	0.125x0.125mm (1mm=8dots)
	Print Width	104mm (4.09") or 108mm (4.25")
	Print Length	10~2286mm (0.39"~90")
	Printer Dimensions	278x210x180 mm (WxDxH)
	Printer Language	TPLZ
GENERAL	Printer Weight	2.09KG
	Operation Condition	Temperature: 5~45 (41~104), Humidity: 25~85%RH
	Storage Condition	Temperature: -10~50 (-10~140), Humidity: 10%~90%RH
	Pulse excitation	1x108 Pulses
	Print head	50KM
	Power supply	Input: AC 110V/240V Output: DC24V/2.5A, 60W
RIBBON	Ribbon OD	Max.67mm
	Ribbon Length	Max.300 mt.
	Ribbon Core Size	1 inch (25.4mm)
	Ribbon Width	Max.110mm, Min.30mm
	Ribbon Rolling Up Method	Outward Rolling
MEDIA	Media Roll OD	127mm (5")
	Media Type	Continuous, black mark, gap, punched hole, Fan fold labels etc.
	Media Rolling Up Method	Printing side outward rolling
	Media Width	Max.120mm (4.72") Min.20mm (0.78")
	Media Thickness	Max. 0.254mm (10mil) Min. 0.06mm (2.36mil)
	Media Roll Core Size	25.4mm~38mm (1"~1.5")
	Media Gap	Min. 2 mm (0.09")
	Label Length	10~2286mm (0.39"~90")
ACCESSORIES	Auto cutter	Included