



COLOURED LABELS (Red, Yellow, Green, Blue)

Technical data sheet

FACE MATERIAL:

Description: Coated woodfree paper with a matt colour finish
Application: The facestock's surface structure provides excellent toner bonding and print resolution.
Uses: Ideal fro label applications using variable information such as adress, instruction and inventory labels, labels for office use and many other applications.

TECHNICAL DATA	Grammage	Caliper
	80 g/ M2	83 µ
	ISO 536	ISO 534

ADHESIVE:

Description: A general purpose acrylic based adhesive
Performances: The favourable adhesive properties allow the product to be used on a wide range of flat curved substrates, including packaging materials such as cardboard, plastic films and HDPE containers.
Shelf life: 2 years when stored at 22 C° and 50 % RH

TECHNICAL DATA	Application Temperature (min)	Service Temperature (min)	Service Temperature (max)
	° C	° C	° C
	0	-20	+ 80

BACKING PAPER:

Description: One-side coate bleached backing paper
Use: The produt was tightlu defined release characteristics to avoid predispsing during the printing or ciopying process. It ensures optimum layflatness during conversion and end-use under a relatively wide range of conditions.

TECHNICAL DATA	Grammage	Caliper
	g/m2	mm
	55	57

Our recommendations are based on our experience and up-to-date knowledge. As the products are used outside our control, we cannot take the responsibility for any damage which could be caused when using the product. This technical information sheet replaces all ealier ones. All information could be changed without notice.