

KRAFT PAPER LABELS

Technical data sheet

| FACE MATERIAL: | | | | |
|-------------------|----------------------|------------------|----------------|--|
| Description: | Standard ribben, ma | achine glazed, b | rown kraft paj | per made with long fibre resinous pulp |
| Use: | Especially developed | for labels wher | e an authenti | c, natural ecological look is needed. |
| Limitation. | Damp or hot condit | ion should be av | voided | |
| TECHNICAL DATA | Grammage | Caliper | Opacity | |
| | 70 g/ M2 | 98 Micron | 93% | |

| ADHESIVE: | | | | | |
|---------------------------------|----------------------|----------------------------|------------------------|---|------------------------|
| Description: | acrylic, waterborne | Permanent adhe | sive | | |
| Performances | polar surfaces, tole | rating fluctuations | in temperature | elling applications. Pro and humidity on the b ig immersion in ice bu | ottling line and durin |
| Limitation | Non washable | - | | - | |
| | | | | | |
| Shelf life | 2 years from the d | ate of manufactur | e at + 20 C° and | 50% RH | |
| Shelf life | , Tack | Application | Service | Service |] |
| Shelf life TECHNICAL DATA | | | | [| |
| TECHNICAL | , Tack | Application Temperature | Service Temperature | Service | |

| Description: Application: | White glassine wo For reelstock lami | |
|------------------------------|---|---------|
| | Substance | Caliper |
| TECHNICAL DATA | g/m2 | micron |
| | 78 | 69 |

Our recommendations are based on our experience and up-to-date knowledge. As the products are used outside our control, we cannot take the responsability for any damage which could be caused when using the product. This technical information sheet replaces all ealier ones. All information could be changed without notice.