



REMOVABLE WHITE LABELS

Technical data sheet

FACE MATERIAL:

Description: A matt, white woodfree machine finished paper with good opacity ,excellent absorption and superior toner bonding characteristics. The paper is based on ECF pulp

Note. Due to the rigid facestock characteristics combined with this removable adhesive ,it's not recommended for applications on curved, uneven and cylindrical substrates. Also for the use of this product on cardboard can be critical.

TECHNICAL DATA	Grammage	Caliper
	64 g/ M2	0,077 mm
	ISO 536	ISO 534

ADHESIVE:

Description: A special purpose removable, acrylic based adhesive.

Performances The specially formulated removable adhesive features good tack and adhesion performance in combination with superior and clean removability. The adhesive has good UV resistance and relatively long term removability, it allows application at a wide temperature range and retains its removability properties at fairly low temperature.

Shelf life: 2 years, stored at 22 C° and 50% RH

TECHNICAL DATA	Initial Tack	Application Temperature (min)	Service Temperature (min)	Service Temperature (max)
	N- FTM 9	° C	° C	° C
	150N/ m	-15	- 30	+ 80

BACKING PAPER:

Description: A one side coated, bleached kraft paper

Application: This product is designed for the manufacture of A4 sheets for use in laser printers, copiers and monochrome inkjet printers.

TECHNICAL DATA	Grammage	Caliper
	g/m2	mm
	55	0,057