



PLANET LABEL- SUPER GLUE

Technical data sheet

FACE MATERIAL:

Description: A matt, white woodfree machine finished paper with good opacity, excellent absorption and superior toner bonding characteristics. Facestock comes from FSC fibre

Use: The product is ideal for label applications using variable information such as address, instruction and inventory labels, labels for office use and many other applications.

TECHNICAL DATA	Grammage	Caliper
	70 g/ M2	0,080 mm
	ISO 536	ISO 534

ADHESIVE:

Description: A general purpose permanent, acrylic based adhesive.

Performances: The adhesive features good initial tack and adhesion performances on a wide range of substrates, even at low temperature. Suitable for direct contact on dried food and not fat

Shelf life: 2 years stored at 22 C° and 50% RH

TECHNICAL DATA	Initial Tack	Application Temperature (min)	Service Temperature (min)	Service Temperature (max)
	N- FTM 9	° C	° C	° C
	700N/ m	0	- 20	+ 80

BACKING PAPER:

Description: A one side coated bleached kraft paper

Application: This product is designed for the manufacture of A4 sheets for use in laser printers, copiers and monochrome inkjet printers. The product has tightly defined release characteristics to avoid predisping during the printing or copying process. The well balanced laminate construction ensures optimum layflatness during conversion and end-use under a relatively wide range of conditions.

TECHNICAL DATA	Grammage	Caliper
	g/m2	mm
	55	0,057

Our recommendations are based on our experience and up-to-date knowledge. As the products are used outside our control, we cannot take the responsibility for any damage which could be caused when using the product. This technical information sheet replaces all ealier ones. All information could be changed without notice.