



HIGH QUALITY WHITE POLYESTER LABELS

Technical data sheet

FACE MATERIAL:

Description: Special gloss coated PET film.
Use: Multicolour inkjet printing, high resolution Specially designed top coating for SOHO applications with improved ink drying time and good level of water resistance.

TECHNICAL DATA	Grammage	Caliper
	100 g/ M2	80 microns

ADHESIVE:

Description: Acrylic, water borne clear permanent adhesive
Performances Specially designed for filmic face materials. Excellent clarity, UV-stability and good water resistance once labelled. Good adhesion properties and heat resistance.
Shelf life: From the date of manufacture 2 years at + 20 C° and 50% RH

TECHNICAL DATA	Min Tack	Application Temperature (min)	Service Temperature (min)	Service Temperature (max)
	N- FTM 9	° C	° C	° C
	9 N	5	- 20	+ 100

BACKING PAPER:

Description: White woodfree kraft backing paper
Application: Backing paper for reels and sheets in information labelling.

TECHNICAL DATA	Substance	Caliper
	g/m2	micron
	87	82

Our recommendations are based on our experience and up-to-date knowledge. As the products are used outside our control, we cannot take the responsibility for any damage which could be caused when using the product. This technical information sheet replaces all earlier ones. All information could be changed without notice.