



FLUORESCENT LABELS (Red, Orange, Green, Yellow)

Technical data sheet

FACE MATERIAL:

Description: One side woodfree paper with a fluorescent coating.
Application: Suitable for manufacture of A4 sheets for use in Medium speed laserprinters, Desk-Top Inkjet and laserprinters, Dry toner copiers.
Uses: Eye-catching labels for pricing, displays, promotions and warning signs instruction and inventory labels and many others applications

TECHNICAL DATA	Grammage	Caliper
	80 g/ M2	0,085 mm
	ISO 536	ISO 534

ADHESIVE:

Description: A general purpose permanent, acrylic based adhesive
Performances: The adhesive is suitable for general application on a wide range of substrates. The adhesive provides excellent tack and adhesion to most surfaces including packaging materials such as cardboard, plastic films and HDPE containers.
Shelf Life: 2 years when stored at 22 C° / 50% RH

TECHNICAL DATA	Application Temperature (min)	Service Temperature (min)	Service Temperature (max)
	° C	° C	° C
	0	-20	+ 80

BACKING PAPER:

Description: One-side coated, bleached kraft paper
Use: The well balanced laminate construction ensures optimum layflatness during conversion and end-use under a relatively wide range of conditions

TECHNICAL DATA	Grammage	Caliper
	g/m2	mm
	55	0,06