



## SILVER POLYESTER MATT LABELS

### Technical data sheet

#### FACE MATERIAL:

**Description:** Metalized, heat stabilized, matt coated computer imprintable polyester film.  
**Use:** Information labelling where overprinting is made by monochrome laser, thermal transfer. Recommended for electronics and electrical equipment and logistics labelling.

<b>TECHNICAL DATA</b>	Grammage	Caliper
	80 g/ M2	58 Micron

#### ADHESIVE:

**Description:** Acrylic, water bone clear permanent adhesive.  
**Performances** Designed for filmic face materials. Excellent clarity, UV-stability and good water resistance once labelled. Good adhesion properties and heat resistance.  
**Limitations** Limited adhesion at low temperatures  
**Shelf life** From the date of manufacture 2 years in + 20C° and RH 50%

<b>TECHNICAL DATA</b>	Tack (min)	Application Temperature (min)	Service Temperature (min)	Service Temperature (max)
	N- FTM 9	° C	° C	° C
	9 N	5	- 20	+ 100

#### BACKING PAPER:

**Description:** Matt coated kraft backing paper  
**Use:** A4 synthetic applications for laser end-use

<b>TECHNICAL DATA</b>	Substance	Caliper	Opacity
	g/m2	micron	%
	100	88	89

Our recommendations are based on our experience and up-to-date knowledge. As the products are used outside our control, we cannot take the responsibility for any damage which could be caused when using the product. This technical information sheet replaces all earlier ones. All information could be changed without notice.