



TRANSPARENT POLYESTER GLOSSY LABELS

Technical data sheet

FACE MATERIAL:

Description: Transparent. Gloss coated heat stabilised polyester film. Designed for information labelling where overprinting is made by laser or thermal transfer.

Use: Information labelling where overprinting is made by laser or thermal transfer

TECHNICAL DATA

Grammage	Caliper
71 g/ M2	50 Micron

ADHESIVE:

Description: Clear permanent adhesive acrylic, waterborne.

Performances: Designed for filmic face materials. Excellent clarity, UV-stability and good water resistance once labelled. Good adhesion properties and heat resistance.

Limitations: Limited adhesion at low temperatures

Shel life: From the date of manufacture 2 years in +20 C° and RH 50%

TECHNICAL DATA	Tack (min)	Application Temperature (min)	Service Temperature (min)	Service Temperature (max)
	N- FTM 9	° C	° C	° C
	9 N	5	- 20	+ 100

BACKING PAPER:

Description: White woodfree kraft backing paper

Application: A4 applications for laser end-use where high layflat is demanded.

TECHNICAL DATA	Substance	Caliper
	g/m2	micron
	100	97

Our recommendations are based on our experience and up-to-date knowledge. As the products are used outside our control, we cannot take the responsibility for any damage which could be caused when using the product. This technical information sheet replaces all ealier ones. All information could be changed without notice.