



## TRANSPARENT POLYESTER MATT LABELS

### Technical data sheet

#### FACE MATERIAL:

**Description:** Transparent. matt coated heat stabilised polyester film.  
**Use:** Information labelling where overprinting is made by laser, thermal transfer. Recommended for drum and logistics labelling

|                       |          |           |
|-----------------------|----------|-----------|
| <b>TECHNICAL DATA</b> | Grammage | Caliper   |
|                       | 56 g/ M2 | 43 Micron |

#### ADHESIVE:

**Description:** Acrylic water bone clear permanent adhesive  
**Performances** Designed for filmic face materials. Excellent clarity, UV-stability and good water resistance once labelled.  
**Limitations:** Limited adhesion at low temperatures.  
**Shelf life:** From the date of manufacture 2 years in + 20 C° and RH 50%

|                       |            |                               |                           |                           |
|-----------------------|------------|-------------------------------|---------------------------|---------------------------|
| <b>TECHNICAL DATA</b> | Tack (min) | Application Temperature (min) | Service Temperature (min) | Service Temperature (max) |
|                       | N- FTM 9   | ° C                           | ° C                       | ° C                       |
|                       | 9 N        | 5                             | - 20                      | + 100                     |

#### BACKING PAPER:

**Description:** Matt coated kraft backing paper  
**Application:** A4 applications for laser end-use.

|                       |           |         |         |
|-----------------------|-----------|---------|---------|
| <b>TECHNICAL DATA</b> | Substance | Caliper | Opacity |
|                       | g/m2      | micron  | %       |
|                       | 100       | 88      | 89      |

Our recommendations are based on our experience and up-to-date knowledge. As the products are used outside our control, we cannot take the responsibility for any damage which could be caused when using the product. This technical information sheet replaces all earlier ones. All information could be changed without notice.