



## PET MATT SILVER

### Technical data sheet

#### FACE MATERIAL:

**Description:** Top coated, direct metallized, matt-coated polyester film  
**Use:** For durable end-users requiring good resistance against water, oil and chemical, e.g. labelling on a wide range of household, garden and industrial applications.

<b>TECHNICAL DATA</b>	Grammage	Caliper
	51 g/ M2	36 Micron

#### ADHESIVE:

**Description:** Acrylic water borne Clear permanent adhesive.  
**Performances** Designed for filmic face materials. Excellent clarity, UV-stability and good water resistance once labelled. Good adhesion and heat resistance.  
**Limitations:** Limited adhesion at low temperatures  
**Shelf life:** From the date of manufacture 2 years in + 20C° and RH 50%

<b>TECHNICAL DATA</b>	Tack (min)	Application Temperature (min)	Service Temperature (min)	Service Temperature (max)
	N- FTM 9	° C	° C	° C
	9 N	5	- 20	+ 100

#### BACKING PAPER:

**Description:** White high transparent glassine backing paper  
**Application:** Especially designed for filmic label material giving the best conversion properties. Good with photocell dispensing systems.

<b>TECHNICAL DATA</b>	Substance	Caliper
	g/m2	micron
	64	56

Our recommendations are based on our experience and up-to-date knowledge. As the products are used outside our control, we cannot take the responsibility for any damage which could be caused when using the product. This technical information sheet replaces all earlier ones. All information could be changed without notice.