



## TYRE LABEL

### Technical data sheet

#### FACE MATERIAL:

**Description** A white coated, woodfree printing paper with semi-gloss appearance, laminated to a flexible aluminium barrier foil.

TECHNICAL DATA	Weight	Caliper
	g/m <sup>2</sup>	Microns
	781	64

#### ADHESIVE:

**Description** A special purpose permanent, rubber based adhesive.

**Performances** The adhesive is specially designed to meet the performance requirements of automotive tyre labelling. The special composition provides a superb anchorage of the label to the compound curved and extremely irregular surface of tyres, neglecting the negative influences of surface contaminants such as mould release agents or components migrating from the rubber.

**Shelf life** 1 year under the following storage conditions: 20-25 °C ; 40-50 % RH

TECHNICAL DATA	Initial Tack	Application Temperature (min)	Service Temperature (min)	Service Temperature (max)
	N/mm	°C	°C	°C
	45N/25mm	0	-20	+70

#### BACKING PAPER:

**Description** A white, supercalendered glassine paper

TECHNICAL DATA	Weight	Caliper
	g/m <sup>2</sup>	Microns
	78	68

Our recommendations are based on our experience and up-to date knowledge. As the products are used outside our control, we cannot take the responsibility for any damage which could be caused when using the product. This technical information sheet replaces all earlier ones. All information could be changed without notice.