



SECURITY LABEL FOR TT

Technical data sheet

FACE MATERIAL:

- Description** A frangible matt white cast PVC film.
- Use** The product is designed with extreme tamper evidence as priority. The face is frangible, of low caliper- giving little “edge” to pick at- and comfortable/semi squeezable to avoid accidental breakage after application. The excellent durability of face allows its use for indoor and outdoor application.

TECHNICAL DATA	Weight	Caliper
	g/m2	Microns
	112	60

ADHESIVE:

- Description** A permanent solvent acrylic based adhesive.
- Performances** The adhesive is aggressive on a wide range of flat and curved surfaces. These typically include glass, steel, varnished and unvarnished carton boards, and most “plastic” use in packaging and moulding.
- Shelf life** 2 years (20-25 °C ; 40-50% RH)

TECHNICAL DATA	Initial Tack	Application Temperature (min)	Service Temperature (min)	Service Temperature (max)
	N/mm	°C	°C	°C
	16/25	+10	-50	110

BACKING PAPER:

- Description** A white, supercalendered glassine paper

TECHNICAL DATA	Weight	Caliper
	g/m2	Microns
	80	69

Our recommendations are based on our experience and up-to date knowledge. As the products are used outside our control, we cannot take the responsibility for any damage which could be caused when using the product. This technical information sheet replaces all ealier ones. All information could be changed without notice.